

# PIT MASTER SERIES

## PIT MASTER 30 HPS REPLACEMENT LIGHT

#### **500 WATT HPS/METAL HALIDE REPLACEMENT**



PART #	MAR-PMX3040	MAR-PMX3060	MAR-PMX3090
REAM PATTERN	40° Wide	60° Extra Wide	90° Xtreme Wide

#### **Technical Information**

WARRANTY	3 Year
RAW LUMENS	15,540 lm
EFFECTIVE LUMENS	11,344 lm
WATTAGE	150
WEIGHT	11.02 lb/5.6 kg
LED LIFESPAN	50,000 Hours
DIMENSIONS	11.75" x 7.70" x 5.04" 298.5 mm x 195.5 mm x 127.5 mm
INPUT VOLTAGE	18-65V DC
AMP DRAW (24V)	6.2A
IP RATING	IP-69K
VIBRATION RATING	15.6 G <sub>ms</sub>
OPERATING TEMP	-40 Celsius ~ +80 Celsius
LED COLOR TEMPERATURE	5000K

















## **Optional AC/DC Converter**

High voltage inverters support up to 480V of AC input.




PART #	XPC-PS150-24	XPC-PS150-HV-24*
INPUT VOLTAGE	100-277V AC	180-480V AC
OUTPUT VOLTAGE	24V DC	24V DC
WATTAGE	150	150
MAX AMP DRAW (24V)	6.25A	6.25A

<sup>\*</sup>Requires Additional Adapter

## Pit Master 30 Series

The Pit Master series was designed with many applications in mind, from ocean freighters to commercial fishing vessels.





#### **Features**

- Integrated Power Supply Mount (Power Supply Sold Separately)
- · Integrated Electronic Thermal Management
- Industrial Strength Marine Grade Coating
- · Stainless Steel Mounting Bracket
- · Integrated Deutsch Connector
- Die-Cast Aluminum Housing
- · Reinforced Gasketed Bezel
- Reverse Polarity Operation
- Redundant Circuity Design
- · Polycarbonate Lens
- Patent Pending



Available mounts include the Cobra Head Mount, the Flush Mount and the Hanging Mount.



Flush Mount For Low Bay Applications P-PMX30FLUSHMOUNT



Hanging Mount For Hanging Applications P-PMX30HANGINGMOUNT