


Shockwave Dual Panel LED Light



Modular LED Upgrade for Fluorescent

The Shockwave provides a durable fluorescent upgrade for flat mount applications. The Dual Series offers 150° spread for a full lighting spread.

Shockwave Series Usage Guide

Shockwave Dual: Interior house and track lights for shovels, draglines, and harsh building environments. Replaces T8 fluorescent fixture available from 1' to 4' designed specifically for harsh environment.

Technical Information

PART#	Lens	Raw Lumens	Dimensions	Weight	Wattage
MIL-SWD1220	Clear	1,750 lm(ea)	300/118.8/46.6 mm	2.63 kg	20 Watt
MIL-SWD1220F	Frosted	1,750 lm(ea)	300/118.8/46.6 mm	2.63 kg	20 Watt
MIL-SWD2440	Clear	3,500 lm(ea)	600/118.8/46.6 mm	5.26 kg	40 Watt
MIL-SWD2440F	Frosted	3,500 lm(ea)	600/118.8/46.6 mm	5.26 kg	40 Watt
MIL-SWD3660	Clear	5,250 lm(ea)	900/118.8/46.6 mm	7.71 kg	60 Watt
MIL-SWD3660F	Frosted	5,250 lm(ea)	900/118.8/46.6 mm	7.71 kg	60 Watt
MIL-SWD4880	Clear	7,000 lm(ea)	1200/118.8/46.6 mm	10.25 kg	80 Watt
MIL-SWD4880F	Frosted	7,000 lm(ea)	1200/118.8/46.6 mm	10.25 kg	80 Watt



Features

- ▶ Integrated Electronic Thermal Management
- ▶ Weatherproof Deutsch Connector
- ▶ Die-Cast Aluminum Housing
- ▶ Polycarbonate Lens
- ▶ Patent Pending